

**§ 58.316 Conventional churns.**

Churns shall be constructed of aluminum, stainless steel or equally corrosion resistant metal, free from cracks, and in good repair. All gasket material shall be fat resistant, nontoxic and reasonably durable. Seals around the doors shall be tight.

**§ 58.317 Bulk butter trucks, boats, texturizers, and packers.**

Bulk butter trucks, boats, texturizers, and packers shall be constructed of aluminum, stainless steel, or equally corrosion resistant metal free from cracks, seams and must have a surface that is relatively smooth and easily cleanable. All non-metallic product surfaces shall comply with 3-A Standards for Plastic, Rubber, and Rubber-Like Material.

**§ 58.318 Butter, frozen or plastic cream melting machines.**

Shavers, shredders or melting machines used for rapid melting of butter, frozen or plastic cream shall be of stainless steel or equally corrosion resistant metal, free from cracks and of sanitary construction, and readily cleanable.

**§ 58.319 Printing equipment.**

All printing equipment shall be designed so as to adequately protect the product and be readily demountable for cleaning of product contact surfaces. All product contact surfaces shall be aluminum, stainless steel or equally corrosion resistant metal, or plastic, rubber and rubber like material which comply with 3-A standards, except that conveyors may be constructed of material which can be properly cleaned and maintained in a satisfactory manner.

**§ 58.320 Brine tanks.**

Brine tanks used for the treating of parchment liners shall be constructed of noncorrosive material and have an adequate and safe means of heating the salt solution for the treatment of the liners. The tank should also be provided with a satisfactory drainage outlet.

**§ 58.321 Cream storage tanks.**

Cream storage tanks shall meet the requirements of § 58.128(d). Cream storage tanks for continuous churns should be equipped with effective temperature controls and recording devices.

## QUALITY SPECIFICATIONS FOR RAW MATERIAL

**§ 58.322 Cream.**

Cream separated at an approved plant and used for the manufacture of butter shall have been derived from raw material meeting the requirements as listed under §§ 58.132 through 58.138 of this subpart.

[50 FR 34673, Aug. 27, 1985]

**§ 58.323 [Reserved]****§ 58.324 Butteroil.**

To produce butteroil eligible for official certification, the butter used shall conform to the flavor requirements of U.S. Grade AA, U.S. Grade A, or U.S. Grade B, and shall have been manufactured in an approved plant.

**§ 58.325 Anhydrous milkfat.**

If cream is used in the production of anhydrous milkfat that is eligible for official certification, the anhydrous milkfat shall be made by a continuous separation process directly from milk or cream. The cream used shall be comparable to the flavor quality specified above for U.S. Grade AA or U.S. Grade A butter. The milkfat from cream may then be further concentrated into oil. The cream or oil shall be pasteurized in accordance with the procedures for cream for buttermaking (§ 58.334a). If butter is used in the production of anhydrous milkfat that is eligible for official certification, the butter used shall conform to the flavor requirements of U.S. Grade AA or U.S. Grade A butter and shall have been manufactured in an approved plant. The appearance of anhydrous milkfat should be fairly smooth and uniform in consistency.

[60 FR 4826, Jan. 24, 1995]

**§ 58.326 Plastic cream.**

To produce plastic cream eligible for official certification, the quality of the

cream used shall meet the requirements of cream acceptable for the manufacture of U.S. Grade AA or U.S. Grade A butter.

**§ 58.327 Frozen cream.**

To produce frozen cream eligible for official certification, the quality of the cream used shall meet the requirements of cream acceptable for the manufacture of U.S. Grade AA or U.S. Grade A butter.

**§ 58.328 Salt.**

The salt shall be free-flowing, white refined sodium chloride and shall meet the requirements of The Food Chemical Codex.

**§ 58.329 Color.**

Coloring, when used shall be Annatto or any color which is approved by the U.S. Food and Drug Administration.

**§ 58.330 Butter starter cultures.**

Harmless bacterial cultures when used in the development of flavor components in butter and related products shall have a pleasing and desirable flavor and shall have the ability to transmit these qualities to the finished product.

**§ 58.331 Starter distillate.**

The refined flavor components when used to flavor butter and related products. It shall be of food grade quality, free of extraneous material and prepared in accordance with good commercial practice.

OPERATIONS AND OPERATING  
PROCEDURES

**§ 58.332 Segregation of raw material.**

The milk and cream received at the dairy plant shall meet the quality specifications as indicated under § 58.322. The milk and cream should be segregated by quality and processed separately in such a manner that the finished product will fully meet the requirements of a particular U.S. Grade or other specification, whichever is applicable.

**§ 58.334 Pasteurization.**

The milk or cream shall be pasteurized at the plant where the milk or

cream is processed into the finished product or by procedures as set forth by the Administrator.

(a) *Cream for butter making.* The cream for butter making shall be pasteurized at a temperature of not less than 165 °F. and held continuously in a vat at such temperature for not less than 30 minutes; or pasteurized by HTST method at a minimum temperature of not less than 185 °F. for not less than 15 seconds; or it shall be pasteurized by any other equivalent temperature and holding time which will assure adequate pasteurization. Additional heat treatment above the minimum pasteurization requirement is advisable to insure improved keeping-quality characteristics.

Adequate pasteurization control shall be used and the diversion valve shall be set to divert at no less than 185 °F. with a 15 second holding time or its equivalent in time and temperature to assure pasteurization. If the vat or holding method of pasteurization is used, vat covers shall be closed prior to holding period to assure temperature of air space reaching 5 °F. higher than the minimum temperature during the holding time. Covers shall also be kept closed during the holding and cooling period.

(b) *Cream for plastic or frozen cream.* The pasteurization of cream for plastic or frozen cream shall be accomplished in the same manner as in paragraph (a) of this section, except, that the temperature for the vat method shall be not less than 170 °F. for not less than 30 minutes, or not less than 190 °F. for not less than 15 seconds or by any other temperature and holding time which will assure adequate pasteurization and comparable keeping-quality characteristics.

**§ 58.335 Quality control tests.**

All milk, cream and related products are subject to inspection for quality and condition throughout each processing operation. Quality control tests shall be made on flow samples as often as necessary to check the effectiveness of processing and manufacturing and as an aid in correcting deficiencies in processing and manufacturing. Routine analysis shall be made on raw materials and finished products to assure